

Flexio

ESPERO

Thickness	67 mm
Wall height	To 3.100 mm*
Wall width	Single wing: 7.500 mm, double wing: 15.000 mm
Panel width	450 – 900 mm*

C2C certification Bronze

Panel profiles Extremely slim, vertical aluminium profiles.

Colour options Standard upper track is white. Lacquering available in every colour.
Floor track (floor supported): ultra-flat anodised aluminium track profile.

Plating High-grade E1-quality particle board standard with FSC certification.

Finish All materials commonly used in interior construction are available.

Sound insulation Rw rating (laboratory value) 38, 42, and 46 dB

Weight 19 – 32 kg/m²

Available with door Yes, first panel is a door as standard.
Optional: closing panel is available with a cupped handle.

Upper and lower seals Black rubber sealing profiles.

Locking mechanism Panels are alternately locked with one turn of the operation key.

Track The rail height is adjustable in both suspending and supporting setups.

Supported by Top hung: upper track, optional with floor guide.
Bottom roller: floor supported.

Parking Centerfold: under the centre of the track, left and/or right in the opening
Endfold: completely at one side of the track, left and/or right in the opening

Environmental requirements Only suitable for indoor use.
Relative humidity of 60% should not be exceeded.

* other specifications available on request