

<b>Profile thickness</b>	45 mm
<b>Glass thickness</b>	To height 3.000 mm (inclusive): 10 mm, 3.000-3.500 mm: 12 mm
<b>Wall height</b>	To 3.500 mm*
<b>Wall width</b>	No limits
<b>Panel width</b>	1.250 mm*
<b>C2C certification</b>	Bronze
<b>Panel profiles</b>	The only profiles are the horizontal ones at the top and bottom, which are both 100 mm in height.
<b>Colour options</b>	Standard model is available in technically anodised aluminium. Lacquering in every colour available.
<b>Weight</b>	10 mm glass (up to height of 3000 mm): 26 kg/m <sup>2</sup> 12 mm glass (from height 3000 mm): 31 kg/m <sup>2</sup>
<b>Available with door</b>	Yes, with 2-point suspension
<b>Panel-to-panel connection</b>	Optional: aluminium U-profile including rubber seal.
<b>Upper and lower seals</b>	Standard: upper seal. Optional: upper and lower seals.
<b>Locking mechanism</b>	Manual, invisible locking mechanism at the bottom. The locking mechanism connects the panels together to create a stable setup.
<b>Supported by</b>	Upper track
<b>Track and wheels</b>	Bearing-mounted hard-plastic wheels that run along the hard-aluminium track profile.
<b>Parking</b>	1-point suspension (in the opening, under main track) or 2-point suspension (available with parking elsewhere).
<b>Environmental requirements</b>	Only suitable for indoor use. Outdoor use available on request.

\* other specifications available on request